

Change for Life




Lomo

INVERTER



- Class A Efficiency
- 0.5W Standby Power
- On/Off LED Display
- Gold Fin Condenser



SYSTEM			GWH09QB-K3DNB6B	GWH12QC-K3DNB6B	GWH18QD-K3DNB6B	GWH24QE-K3DNB6B	GWH28QB-K3DNB6B	GWH36QC-K3DNB2N
Power supply			220-240V- 50Hz, 1Ph					
Cooling	Capacity (min-max)	Btu/h	9000 (1500-11000)	12000 (2000-14000)	18000 (5700-19200)	22000 (6800-28000)	27000 (8000-30000)	34000 (10000-37000)
	Input Watt	W	825	1090	1640	2010	2500	3500
	Input current	A	3.7	4.8	7.28	8.9	11.6	16.0
	EER	W/W	3.21	3.21	3.21	3.21	3.21	2.86
	RSA Efficiency Class	W/W	A	A	A	A	A	C
Heating	Capacity (min-max)	Btu/h	9600 (1500-14000)	13000 (2000-17500)	19000 (5300-22280)	23000 (8180-27300)	3000 (9000-32000)	37500 (12000-4000)
	Input	W	775	1050	1540	1870	2790	3600
	Input current	A	3.7	4.7	6.8	8.3	13.1	16.5
	COP	W/W	3.61	3.62	3.62	3.61	3.15	3.06
	Efficiency Class	W/W	A++	A++	A++	A++	B	B
Rated input	W	1420	1650	1640	2010	3900	4000	
Rated current	A	6.9	6.9	11	12	11.6	18.0	
Refrigerant type	g	R410A/740g	R410A/1000g	R410A/1200g	R410A/1350g	R410A/2000g	R410A/2600g	
Refrigerant piping	Liquid / Gas	inch	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	1/4" / 5/8"	1/4" / 5/8"	3/8" / 5/8"
	Max length	m	20	20	20	25	25	25
	Max height	m	10	10	10	10	10	10
Setting temperatures	°C	16-30	16-30	16-30	16-30	16-30	16-30	
Usable Ambient Temperatures	Outdoor(cool/heat) °C	18-43 / -10-24						
Indoor model			GWH09QB-K3DNA1B/I	GWH12QC-K3DNA1B/1	GWH18QD-K3DNA1B/1	GWH24QE-K3DNA1B/1	GWH28QB-K3DNA1B/I	GWH36QC-K3DNA2M/I
Indoor airflow (Hi/Med/Low)	m3/h	560/490/430/330	600/540/460/330	850/800/700/570	1100/1000/950/850	1400/1250/1000/850	1600/1300/1100/850	
Indoor sound pressure (Hi/Med/Low)	dB(A)	39/36/32/28	41/37/33/29	47/43/39/35	46/44/40/36	52/48/41/37	41/37/33/29	
Indoor unit	Dimension(W*H*D)	mm	790x275x200	845x289x209	970x300x224	1078x325x246	1078x325x246	845x289x209
	Packing (W*H*D)	mm	866x367x271	921x379x281	1041x320x383	1148x350x413	1148x350x413	921x379x281
	Net/Gross weight	Kg	9/11	11/13	13.5/16.5	16/19.5	16.5/20	18.5/23
Outdoor model			GWH09QB-K3DNA1B/O	GWH12QC-K3DNA1B/O	GWH18QD-K3DNA1B/O	GWH24QE-K3DNA1B/O	GWH28QB-K3DNA1B/O	GWH36QC-K3DNB4M/O
Outdoor sound pressure	dB(A)	49	51	55	56	59	61	
Outdoor unit	Dimension(W*H*D)	mm	710x550x318	710x550x319	899x596x378	965x700x396	965x700x396	1003x790x427
	Packing (W*H*D)	mm	774x351x607	774x351x607	948x420x645	1029x750x458	1029x750x458	1083x855x488
	Net/Gross weight	Kg	28/30	30/32	41/44.5	46/51	54/58	65/70

FEATURES

Child Lock

Self Diagnostics

Comfy Sleep Mode

Ambient Temp Display

170v – 265v operating voltage



 **GOLD FIN**



REMOTE CONTROL 